



The DV4 and DV4 HD Digital Signage Systems



The DV4 Standard Definition Digital Sign Player

The DV4 HD Full High Definition Digital Sign Player



The DV4 Generation of Digital Sign Players Feature:


- Hundreds of PowerPoint® backgrounds ready for you to add text
- Ability to easily add your own backgrounds or images to a playlist
- The ability to play stills, PowerPoint® image presentations and video files
- Easy to use sign management software
- Sign Management software converts PowerPoints® to still images for playback
- Scheduling of files by Time of Day and Day of Week or repeating loop
- Built in remote access by LAN or Internet via IP address
- Solid state circuitry for long life and dependability
- 4 GB Flash Memory
- Unequaled service and support

DV4 Standard Definition Pro Multimedia Player



The DV4 is a powerful communications tool that lets you schedule and display high impact video, stills and PowerPoint® image presentations over local and remote standard Definition TV screens. It is perfect for Hotels, Restaurants, Hospitals, Senior Care, Condos, Schools, Government & Corporate Offices, Cable Companies and more! Simply add your media, schedule and export your presentation to the DV4.

DV4 Specifications

Video Codec Support	MPEG 1 MP@ML 480P MPG MPEG 2 MP@ML 480P MPG MPEG 4 ASP@L2 480P AVI
Image Codec Support	JPEG 640X480
Management Options	VMC Manager Express
I/O Ports 	VGA Out S-Video Out Composite Out 3.5 mm Stereo Audio Jack CF Card Slot
Local Storage	CF Card (4GB card supplied) Holds Approx. 180 minutes of video @3Mbps
Power Requirements	AC Power Adaptor output: 5V, 2A DC Power Consumption: 10W max. 5W avg.
Environmental	Operating Temperature: 0 to 40 deg C Humidity: 5-85%RH @ 40 deg C
Dimensions	133.5 X 113.5 X 25 (mm) (excluding projections) 5.3 X 4.4 X 1 (inches (excluding projections))
Weight	1.1 lbs.

DV4 HD (1080p) Pro Multimedia Player



DV4 HD 1080p Player

The DV4 HD offers true 1080p High Definition for unsurpassed clarity & detail. It can be controlled locally or remotely via LAN or WAN through VMC's content manager network.



The DV4 HD Offers Some Unique Features:

- More than 100 HD PowerPoint® Backgrounds are included.
- The split screen capability includes more than a dozen alternatives
- Dozens of units can be controlled with our simple manager interface
- WAN capability allows hundreds of signs to be centrally controlled
- Schedule and display an external video and audio source
- The Manager Software automatically converts PowerPoint® to stills

DV4 HD Specifications

Video format support	POPAI Screen Media Standards S6 (MPEG-1 SIF, 3Mbps CBR) S7 (MPEG-1 480p, 10Mbps CBR) S8 (MPEG-1 720p, 15Mbps CBR) S9 (MPEG-2 480p, 6Mbps CBR) S10 (MPEG-2 720p, 12Mbps CBR) S11 (MPEG-4 AVC, 480p, 6Mbps CBR) S12 (MPEG-4 AVC, 720p, 10Mbps CBR) E4 (VC-1/WMV9, MP@ML, 720p)* E5 (VC-1/WMV9, MP@HL, 1080p)* E6 (MPEG-2, 1080p, 20Mbps CBR) E7 (MPEG-4 ASP, 480p, 10Mbps CBR) E8 (MPEG-4 AVC, 1080p, 25Mbps CBR) *wmv video only	Playback control	W3C SMIL 3.0 (sub-set): multi-zone, wall-clock, sequential, parallel, and exclusive scheduling	
Image format support	POPAI Screen Media Standards S1 (JPEG 480p baseline) S2 (JPEG 720p baseline) S3 (JPEG 1080p baseline) E1 (PNG 24bpp+alpha, 480p) E2 (PNG 24bpp+alpha, 720p) E3 (PNG 24bpp+alpha, 1080p)	Content management method	LAN – VMC Manager Express USB direct update WAN – Optional Content Manager network	
Audio codec support	POPAI Screen Media Standards S4 (MPEG L2 audio) S5 (MP3 audio, 384Kbps)	Physical I/O connectors	HDMI 1.2 (Full-HD 1080p) DVI-D (via 3rd-party HDMI-DVI converter) VGA RCA audio L/R Ethernet copper 10/100 BASE-T USB 2.0	
		Local storage	4GB SLC high performance CF Card (Holds up to 1.8 hrs of typical 5 Mbps Hi Def. video)	
		Accessories	RCA male-3.5mm female audio cable 3.5mm male-male audio cable Ethernet cable Wall-mount bracket VESA mounting kit (Optional)	
		Power requirement	12V, 2A DC	
		Power consumption	Typical* 7W	Typical* 5W
		Environmental	Operating temperature: 0 – 40° C / 32 – 104° F	